

LEDSPARKS*

LINEAR LED SUSPENSION OR SURFACE MOUNT



Available Voltage: 120-277V AC

Features:


- Various connection methods available.
- Wider luminous surface and soft output light. No glare!
- High efficient, high CRI and more comfortable .

Overview:

This OLL is the latest designed and developed LED linear lighting, most suitable for various modern and minimalist decoration venues. With its hanging installation method its height is flexible and adjustable. You can be creative with our thoughtfully designed connecting components and light up to the actual space of your room by using many different combination of connecting shape as "I" "L" "T" "+" etc. It has various combination forms which are flexible, inter-changeable and with infinite originality. We bring a light with intelligence into your life.


Applications:

Open plan office, no false-ceiling or dropped ceiling building, meeting room, warehouse, artistic design room where it needs minimalist decoration and modern style.



Package

Size (CM)	Net Weight (KG)	Quantity/ Carton(PCS)
32×52×12	8.3	20
47×52×12	10.6	20
62×53×13	15.3	20
122×53×13	25.7	20



Height	Emax	Angle: 116.00deg	Diameter
1m	1049lx		320.1cm
2m	262.2lx		640.19cm
3m	116.5lx		960.29cm
4m	65.56lx		1280.39cm
5m	41.96lx		1600.48cm

Specification

Item	LED	Total Power	Voltage	CCT	Lumen ± 10%	Efficacy	CRI
0.3M	SMD	10W	120-277V AC	3000K	850LM	>85LM/W	>80
				4000K	920LM	>92LM/W	>80
				5000K	950LM	>95LM/W	>80
0.45M	SMD	15W	120-277V AC	3000K	1250LM	>83LM/W	>80
				4000K	1370LM	>91LM/W	>80
				5000K	1400LM	>93LM/W	>80
0.6M	SMD	20W	120-277V AC	3000K	1700LM	>85LM/W	>80
				4000K	1770LM	>88LM/W	>80
				5000K	1800LM	>90LM/W	>80
1.2M	SMD	35W	120-277V AC	3000K	2975LM	>85LM/W	>80
				4000K	3150LM	>90LM/W	>80
				5000K	3200LM	>91LM/W	>80
1.2M	SMD	45W	120-277V AC	3000K	3825LM	>85LM/W	>80
				4000K	4150LM	>92LM/W	>80
				5000K	4275LM	>95LM/W	>80



261 NW 23rd Street
Miami, FL 33127
Office 305.571.8079
1-800-571-4LED

LEDSPARKS*

WWW.LEDSPARKS.COM